Nissan x trail 2014 user manual

I'm not robot!

chancing the joy of being behind the wheel and turning the wail acts as your driving partner, always looking out for you are Nissan X-TRAIL can adapt to changing conditions 30 times etter. Looking for excellent fuel economy in a roomy crossover.	eve and integrate cars in the world around us. It's bringing you a world into a safer place everyday. Meet your co-driver. It sees and those around you. The Nissan X-TRAIL is so agile and respons faster than the blink of an eye. Whether it's sand or gravel, rainer that's lots of fun to drive? That's what you get with the new Nice petrol & highly efficient 1.6 litre diesel engine. The diesel offer	d it senses. Smart safety features step in on you sive, it actually improves your driving. Nissan's a-covered surfaces or a tight turn, the system wissan X-TRAIL. From exterior aerodynamics that	r behalf, from Intelligent Auto headlights, Intelligent Emer Chassis Control technologies make it smooth to handle an Il automatically send power to the wheels that need it the whisper through the wind to advanced engines and a virt	gency Braking, Intelligent Forward Collision warning secure to drive – ensuring an exciting yet comfort most. Even in ideal conditions, the Nissan X-TRAIL's ually gearless XTRONIC transmission, it takes effici	ng and Intelligent Lane Departure Intervention, the new Nissan able journey for everyone on board. So get inside and have some sAWD system pays big dividends: getting a grip has never felt ency and performance to the next level. The Nissan X-TRAIL has
all away. The 2.5 petrol engine is mated with the latest versice eir zero-gravity-inspired seats with spinal support, Nissan's exceptional comfort and less fatigue on the long distance trips epair Manual Download Nissan X-Trail T31 Electronic Works wher's Manual Download Nissan X-Trail 2016 Owner's Manu	on of XTRONIC CVT (Continuously Variable Transmission) with usengineers looked to the cosmos. They recreated the relaxed post of your adventures. Nissan X-Trail 2000 Service & Repair Manual hop Manual Download Nissan X-Trail T32 Service repair manual al Download Nissan X-Trail Diesel 2015 Owner's Manual Download. The 60/40 split seat slides forward for easy access and adjusts	up to 40% reduced friction and the ratio coverage cure of astronauts floating in space by designing tal Download Nissan X-Trail 2001 Electronic Rep I Download Nissan X-Trail 2011 Owner's Manual toad Nissan X-Trail Hybrid 2015 Owner's Manual	ge is increased to greater than that of some 8-speed autom an articulated front seat that supports you from the pelvi pair Manual Download Nissan X-Trail 2007 Electronic Rep I Download Nissan X-Trail 2012 Owner's Manual Download I Download Nissan X-Trail Hybrid 2016 Owner's Manual I	natics. The result is an engaging drive and smooth p is to the chest optimizing the blood flow, and seat cu lair Manual Download Nissan X-Trail 2007 Service & d Nissan X-Trail 2013 Owner's Manual Download N Download Nissan X-Trail Hybrid 2017 Owner's Manu	erformance, it's like riding a continuous wave of power. o designations that provide better pressure distribution. The result is Repair Manual Download Nissan X-Trail 2007-2010 Service & issan X-Trail 2014 Owner's Manual Download Nissan X-Trail 20 all Download Nissan X-Trail Service Manual Thanks to the Nissan X-Trail Manual Ma
ves you additional versatility. Perfect for accommodating extra proved Accessories. Whether it's towing the campervan, che ad advanced autonomous tech, to innovative interiors. This natural 4Dogs concept, the trunk has been modified to seat two saily enter the trunk, which has plenty of pet luxuries, including	ra passengers and their gear, it also folds down completely to making your tyre pressure or connecting your favourite music placew Nissan X-Trail concept crossover, on the other hand, doesn't furry friends. Nissan It's the array of dog-friendly features that any a bed, no-spill water bowl and treat dispenser. There's even a creen in the trunk. Nissan Before you think Nissan has gone bar	ake a flat cargo floor for maximum storage capa ylist, the versatile range of Nissan Approved Ac cater for humans - it's designed primarily for do set the X-Trail 4Dogs concept apart. A 360-deg a safety seatbelt, or rather a clip-on harness hoo	city. Nissan X-Trail Repair Manual From the city streets to cessories ensures all your road trip needs are covered. It's ogs. No, it isn't a car designed to be driven by your canine ree pull-out shower will keep your interior free of muddy to bk. Our favorite feature, however, has to be the "dog-cam"	the great outdoors, your Nissan X-TRAIL is ready s official: Nissan has gone barking mad. Concept car companion. Instead, the practical design is more do paws after walks, and you can dry your dog off with connected to the X-Trail's NissanConnect infotainn	to take on any adventure, thanks to its versatile range of Nissan's serve a variety of purposes, from showing new design language of friendly than your average car for pet owners. Called the Nisa built-in dryer. There's a slide-away ramp allowing your dog to ent system, allowing both pet and owner to keep tabs on each of
e Nissan X-Trail 4Dogs are really well-considered, and make buld Nissan be onto something here? Nissan This is a preview anual further down the page underneath the image of the co struments and controls 2 Pre-driving checks and adjustment lts and Supplemental Restraint System (SRS) 0-2 Exterio	it perfect for taking pets out in all weathers," said vet practione we sample and it is limited to 30 pages. On purchase you will receiver. Clicking on the "view full screen" button will take you to a fixed 3 Display screen, heater and air conditioner, and audio 4 systems front	er Rachel Homeny. "In particular, the wash and exive the complete document. Share the publicate ull screen version of the manual. Manufacturer: om Starting and driving 5 In case of emergency of the control of the con	dry functionality allows dogs to be dogs, so owners don't r ionSave the publication to a stackLike to get better recom Nissan Model: X-Trail Table of Contents Condition: 'Exce 6 Appearance and care 7 Maintenance and do-it-yourself 8	need to worry about messing up the car interior. This imendations The publisher does not have the license pt for China'/ (1,1) Illustrated table of contents 0 Sa Technical information 9 Index 10 [Edit: 2014/ 11/ int	s is a great concept that caters to the needs of man's best friend to enable download You can view the 2014 Nissan X-Trail ownerety D seats, seat belts and supplemental 1 restraint system 7 Model: T32-A] (2,1) (5,1) 0 Illustrated table of contents Seats Cockpit
ght-Hand Drive (RHD) model	0-6 Left-Hand Drive (LHD) model	0-10 Engine compartment	USOFIX child restraint system (SRS) T32A130827-10AA20 ISOFIX child restraint system (for second row 1-27) 5.Ch contents Condition: 'Except for China'/ [Edit: 2014/11/7em (P.3-20)*: if equipped JVC0642X 1. Engine hood (P.3-20)	model	R20DD engine model
D Tire placard (P.9-9) Illustrated table of contents 0-3 Con bunted stop light DBulb replacement (P.8-28) 4.Antenna (P.4 Rear combination light (P. 8-27) 10.Fuel filler lid (P.3-27) 11 2-62) D Microphone* (P.4-78, P.4-84, P.4-87, P.4-94, P.4-98	duid (P.8-19) 11. Sonar (parking sensor) system* (P.5-50) 3. Head dition: 'Except for China'/ [Edit: 2014/11/7 Model: T32-A] (8,1 -43) 5.Roof rail* (P.2-60) 6.Parking sensor (sonar) system* (P.5-Child safety rear door locks (P.3-7)*: if equipped Condition: 'Ex) 4.Sunroof* (P.2-52) 5.Cancel switch for ultrasonic and tilt sensutlet (P.2-53) D Spare tire (P.6-2)*: if equipped JVC0654X 7.Roof) EXTERIOR REAR T32A130827-BA5074E9-D21-50) DPark Assist (PA)* (P.4-17) 0-4 Illustrated t cept for China'/ [Edit: 2014/ 11/ 7 Model: T32-Aors* (P.3-20) 6.Sun visors (P.2-61, P.3-29) Cond	C-4E66-B0EF-AE9C682D0BE4 JVC0599X 1.Rear window able of contents 7.Rear fog light* (P. 2-46) 8.Back door (P. A.] PASSENGER COMPARTMENT T32A130827-640688FC ition: 'Except for China'/ (9,1) 12. Front cup holders (P.2-5	defogger (P.2-49) 2.Rear window wiper and washer 3-23) DIntelligent Key system* (P.3-10) DRemote ke-866B-4E18-8CE1-364B86D3233C 1.Inside rearview (5)/Ashtray* (P.2-54) 13. Heated seat switch* (P.1-4)	DSwitch operation (P.2-49) DWindow washer fluid (P.8-19) 3.H cyless entry system* (P.3-7) DRear view camera* (P.4-7, P.4-10) mirror (P.3-28) 2.Sunglasses holder (P.2-55) 3.Front map light 14. Console box (P.2-55) 15. Luggage room D Storages (P.2-54)
tch* (P.3-6) ĐOutside rearview mirror remote control switch SET switch (P.2-7, P.2-8) 3. Headlight and turn signal switch nds-Free Phone System (with navigation)* (P.4-94) 5. Steering 5-43) DSpeed limiter switches* (P.5-41) DBluetooth® Hands Vehicle Dynamic Control (VDC) OFF switch or Electronic Steering Ste	h (Driver's side) (P.3-29) Illustrated table of contents 0-5 [Edit: n (P.2-39)/Fog light switch* (P.2-45) 4. Steering-wheel-mounted on wheel (P.3-28) DHorn (P.2-50) 6. Wiper and washer switch (P. s-Free Phone System (without navigation)* (P.4-78, P.4-84, P.4-84) tability Program (ESP) OFF switch (P.5-27) 11. Headlight aiming switch* (P.3-24) 19. Push-button ignition switch (model with Intel	2014/11/7 Model: T32-A] COCKPIT GUID-104 ontrols (left side) ĐAudio control* (P.4-76 or Na 2-47) 7.Hazard indicator flasher switch (P.6-2) (37) ĐBluetooth® Hands-Free Phone System (wit control switch* (P.2-42) 12.Parking brake (Ped	73ED5-F428-4070-A4B6-3AE4A1D1CCC6 LEFT-HAND DF vigation system **) DVehicle information display control (0-6 Illustrated table of contents Condition: 'Except for Chich navigation)* (P.4-94) DVoice recognition system switch type)* (P.3-30) 13.ECO switch* (P.5-47) 14.Headlight closes	NVE (LHD) MODEL GUID-5B92FB7E-BFCD-4E4C-9 P.2-20) JVC0643X DBluetooth® Hands-Free Phone na'/[Edit: 2014/11/7 Model: T32-A] (10,1) 8.Steen (P.4-98) 9.Shift lever DContinuously Variable Transeaner switch* (P.2-44) 15.Parking sensor (sonar) sys	506-C5094664CBDF 1.Instrument brightness control (P.2-10) 2. System (without navigation)* (P.4-78, P.4-84, P.4-87) DBluetootling-wheel-mounted controls (right side) DCruise control switcher smission (CVT) (P.5-13) DManual Transmission (MT) (P.5-17) tem OFF switch* (P.5-51) 16.Power back door switch* (P.3-24)
f equipped **: See the separate Navigation System Owner's DBluetooth® Hands-Free Phone System (without navigation ton ignition switch (model with Intelligent Key system)* (P. vigation)* (P.4-94) DVoice recognition system switch* (P.4-94) ntrol (VDC) OFF switch or Electronic Stability Program (ES)	Manual (if equipped). RIGHT-HAND DRIVE (RHD) MODEL GUI on)* (P.4-78, P.4-84) DBluetooth® Hands-Free Phone System (w. 5-9) 6.Steering-wheel-mounted controls (right side) DCruise con 8) 7.Wiper and washer switch (P.2-47) or Headlight and turn sig P) OFF switch (P.5-27) 13.Four-Wheel Drive (4WD) mode switch by system)* (P.5-7) 19.Stop/Start or Idling Stop OFF switch* (P.5-	D-2C73B5AA-609C-4CA5-AC9C-A8EFFF6B2BC ith navigation)* (P.4-94) Condition: 'Except for C trol switches* (P.5-43) DSpeed limiter switches mal switch (P.2-39)/Fog light switch* (P.2-45) 8. * (P.5-22) 14.Shift lever DContinuously Variable	F 1.Hill descent control switch* (P.5-30) 2.Steering-wheel- China'/ JVC0649X 3.Hazard indicator flasher switch (P.6-2) * (P.5-41) [Edit: 2014/11/7 Model: T32-A] (11,1) DBluet Power back door main switch* (P.3-24) 9.Power back door * Transmission (CVT) (P.5-13) DManual Transmission (MT	mounted controls (left side) ĐAudio control* (P.4-76) 4.Headlight and turn signal switch (P.2-39)/Fog ligoth® Hands-Free Phone System (without navigation switch* (P.3-24) 10.Instrument brightness control (P.5-17) 15.Parking brake (Switch type)* (P.3-30) 1	or Navigation system **) DVehicle information display control ht switch* (P.2-45) or Wiper and washer switch (P.2-47) 5.Pushn)* (P.4-78, P.4-84) DBluetooth® Hands-Free Phone System (wi(P.2-10) 11.TRIP RESET switch (P.2-7, P.2-8) 12.Vehicle Dynam 6.Steering wheel (P.3-28) DHorn (P.2-50) 17.Parking brake (Ped
le of contents 0-7 INSTRUMENT PANEL GUID-6AB30B05-1 ear view monitor* (P.4-7) ĐAround view monitor* (P.4-10) E lood release handle (P.3-22) 9.Steering wheel lock lever (P. hter* (P.2-53) 14.Defogger switch (P.2-49) 15.Glove box (P.2 ludio system* (P.4-35) or Navigation system** ĐRear view n	199D-4C45-BA41-DAF524C5659F LEFT-HAND DRIVE (LHD) MCDBluetooth® Hands-Free Phone System (without navigation)* (P3-28) 0-8 Illustrated table of contents Condition: 'Except for Chird-54) 16.Fuse box cover* (P.8-24) *: if equipped **: See the separationitor* (P.4-7) DAround view monitor* (P.4-10) DBluetooth® H	DDEL T32A130827-288FF21B-7739-4FAD-8E2C .4-78)	-DC0FB640F389 JVC0663X 1.Side ventilator (P.4-26) 2.Mo (with navigation)* (P.4-94) ĐVoice Recognition System* (P.4-94) Driver's front-impact air bag (P.1-27)/Horn (P.2-50) 11.Hepped). RIGHT-HAND DRIVE (RHD) MODEL T32A130827-P.4-78) ĐBluetooth® Hands-Free Phone System (with nav	eters and gauges (P.2-7)/Clock (P.2-22) 3.Center ver 2.4-98) 5.Passenger's front-impact air bag (P.1-27) 6 ater/air conditioner control (P.4-26) 12.Auxiliary in 2C6B73CA-1866-4562-9175-5F11892A2EE0 1.Side rigation)* (P.4-94) Condition: 'Except for China'/ (13	utilator (P.4-25) 4.Audio system* (P.4-35) or Navigation system*: Fuse box cover (P.8-24) 7.Fuel filler lid release handle (P.3-27) out jack* (P.4-75) and USB port* (P.4-75) 13.Power outlet*/Cigar ventilator (P.4-26) 2.Passenger's front-impact air bag (P.1-27) 1) 9. Power outlet*/Cigarette lighter* (P.2-53) 10. Auxiliary input
atilator (P.4-25) 5.Meters and gauges (P.2-7)/Clock (P.2-22) achometer (P.2-8) 2.Warning/indicator lights (P.2-12) 3.Veh GINE COMPARTMENT T32A130827-5B4D951A-E33B-40B3 10. Radiator cap (P.8-8) 4. Brake fluid reservoir (P.8-16) Đ 2A130827-0469BBE0-67EA-4CAC-8CA8-6DA80E9EE1CA JV	-49) 12. Steering wheel lock lever (P.3-28) 13. Hood release han 6.Driver's front-impact air bag (P.1-27)/Horn (P.2-50) 7.Glove be cicle information display (P.2-20) D Odometer/twin trip odometer 3-B46A-59CAD646A8B4 QR25DE ENGINE MODEL T32A130827 LHD model D Vehicle overheat (P.6-10) 5. Air cleaner (P.8-17) 1 C0592X 1. Engine coolant reservoir (P.8-9) 7. Engine drive belts (P.6-10) 1 and (P.8-10) 1 and (P.8-10) 1 and (P.8-10) 1 and (P.8-10) 2 and (P.8-10) 2 and (P.8-10) 3.	ox (P.2-54) ĐFuse box (P.8-24) 8.Heater/air cond r (P.2-7, P.2-8) 4.Speedometer (P.2-7) 5.Engine r-690FA407-2649-46DA-9338-40A3EC16529D JV 1. Fuse/fusible link box (P.8-24) 6.Battery (P.8-24) (P.8-14) 2. Brake and clutch* fluid reservoir (P.8-24)	litioner control (P.4-26) Illustrated table of contents 0-9 [15 coolant temperature gauge (P.2-9) 6.Fuel gauge (P.2-9) 0-C0580X 1. Engine coolant reservoir (P.8-9) 8. Engine driv 20) 7.Window washer fluid reservoir (P.8-19) Illustrated to 8-16) D 8. Radiator cap (P.8-8) RHD model D Vehicle over	Edit: 2014/11/7 Model: T32-A] METERS AND GAU 10 Illustrated table of contents Condition: 'Except for e belts (P.8-14) 2. Brake fluid reservoir (P.8-16) DR able of contents 0-11 Condition: 'Except for China'/[Theat (P.6-10) 3. Brake and clutch* fluid reservoir (F	GES T32A130827-085CACB4-087F-44F7-8187-1F542FC0BFEF or China'/ (14,1) JVC0581X [Edit: 2014/ 11/ 7 Model: T32-A] (19 HD model 9. Engine oil dipstick (P.8-10) 3. Engine oil filler cap Edit: 2014/ 11/ 7 Model: T32-A] (16,1) MR20DD ENGINE MOD 8.8-16) D LHD 9. Engine oil dipstick (P.8-10) model 10. Engine o
1B5BC31993 JVC0640X 1. Engine coolant reservoir (P.8-9)	Fuse/fusible link box (P.8-24) *: For Manual Transmission (MT) 7. Engine drive belts (P.8-14) 2. Brake and clutch* fluid reservoir (P.8-19) Illustrated table of contents 0-13 Condition: 'Excerning to the second restraints and the second row seats are conditions of the second row seats and restraint installations. 1-8 Adjust are conditions are conditions of the second row seats and the second row seats are conditions. 1-20 Child restraint installations.	r (P.8-16) D 8. Engine oil dipstick (P.8-10) RHD	model 9. Battery (P.8-20) 3. Engine oil filler cap (P.8-10)	10. Fuse/fusible link box (P.8-24) 4. Brake and clutc	n* fluid reservoir (P.8-16) D LHD *: For Manual Transmission (NA 1 (19.1) 1 Safety D seats, seat helts and supplemental restrain
S) 1-27 Supplemental air bag systems ATS T32A130827-544A337B-5822-4F19-AD26-8D99DEA601	d restraints	1-34 Pre-tensioner seat belt syst le with the seatback reclined. This can be dange	rous. The shoulder belt will not be properly against the bo	ment procedure 1-3/ Conc ody. In an accident, you and your passengers could l	oe thrown into the shoulder belt and receive neck or other serio
ay move suddenly and could cause the loss of control of Se ID-22018305-9BAB-4201-B6FC-C08EB94AEAE0 1.Pull up to the seatback in position. The reclining feature allows the seatback an auto-reset overload protection circuit. If the	ection while the vehicle is in motion, the seatback should be uprest the vehicle. When adjusting the seat positions, be sure not to the adjusting lever *1 . 2. Slide the seat to the desired position. 3. adjustment of the seatback for occupants of different sizes to he motor stops during the seat adjustment, wait 30 seconds, then a lever to adjust the seat height until the desired position is achieved.	contact any moving parts to avoid possible inju- Release the adjusting lever to lock the seat in p lp obtain the proper seat belt fit. (See ^a Seat bel- reactivate the switch To avoid discharge of the	ries and/or damages. 1-2 Safety D seats, seat belts and surposition. Reclining: GUID-22018305-9BAB-4201-B6FC-C08 ts ^o (P.1-9).) The seatback may be reclined to allow occupate battery, do not operate the power seats for a long period	pplemental restraint system Condition: 'Except for CEB94AEAEO 1.Pull up the adjusting lever *2 . 2.Tilt nts to rest when the vehicle is parked. Operating tip of time when the engine is not running. JVRO332X	China'/ [Edit: 2014/11/7 Model: T32-A] Forward and backward the seatback to the desired position. 3.Release the adjusting levers: GUID-22018305-9BAB-4201-B6FC-C08EB94AEAE0. The power lifter (if equipped): GUID-22018305-9BAB-4201-B6FC-
ne either. They could unknowingly activate switches or converge forward or backward the adjusting switch *1 to the desirant belts ^o (P.1-9).) The seatback may be reclined to allow occurred to allow the seather to allow occurred to allow be allow below the switch as a blanket, cushion, seat cover, etc. Other use gasoline, thinner, or any similar materials. SECOND	trols and inadvertently become involved in a serious accident and red position. Reclining: GUID-22018305-9BAB-4201-B6FC-C08E cupants to rest when the vehicle is parked. JVR0334X Seat lifter and the support feature provides lower back support to the driver. Inter console can be operated independently of each other. 1. Standicator light *3 will illuminate when low or high is selected. 3. To the sure you leave the vehicle, be sure to turn off the switch. The erwise, the seat may become overheated. Do not place anything a ROW SEATS T32A130827-3C944850-5F36-4EC0-8FC1-B5D474	d injure themselves. Safety D seats, seat belts a B94AEAE0 Move forward or backward the adjust (if equipped): GUID-22018305-9BAB-4201-B6F Push each side of the adjusting switch to adjust art the engine. 1-4 Safety D seats, seat belts and turn off the heater, return the switch to the lecator of the capture. The battery could run down if the seat or heavy on the seat or pierce it with a pierobeta pierce.	and supplemental restraint system 1-3 Condition: 'Except fixing switch *2 to the desired position. The reclining feature C-C08EB94AEAE0 JVR0119X Pull up or push down the addithe seat lumbar area until the desired position is achieved supplemental restraint system Condition: 'Except for Chievel position. Make sure the indicator light turns off. The heat heater is operated while the engine is not runningDo nor similar object. This may result in damage to the seat 1008-4E61-8F01-E53BD4BE934E JVR0330X Forward and b	for China'/ [Edit: 2014/11/7 Model: T32-A] Forward re allows the adjustment of the seatback for occupation justing switch to adjust the seat height until the desired. Heated seats (if equipped) T32A130827-12F30A0 and [Edit: 2014/11/7 Model: T32-A] 2. Select heat eater is controlled by a thermostat, automatically to not use the seat heater for extended periods or who neater. Any liquid spilled on the heated seat should ackward: GUID-22018305-9BAB-4201-B6FC-C08EB	d and backward: GUID-22018305-9BAB-4201-B6FC-C08EB94A at sof different sizes to help obtain the proper seat belt fit. (See ired position is achieved. Lumbar support (if equipped): GUID-0-21DA-4474-BB84-80C0B5836ADB JVR0322X The front seats or range. For high heat, push the HI (High) side of the switch *1 rrning the heater on and off. The indicator light will remain on a ren no one is using the seat. Do not put anything on the seat which be removed immediately with a dry cloth. When cleaning the seat 44AEAE0 1.Pull up the adjusting lever *1 . 2.Slide the seat to the
ifferent sizes to help obtain the proper seat belt fit. (See as ipped with third row seat: Pull up the lever *1 and pull the of these areas by passengers without proper restraints con the seatbacks. Safety D seats, seat belts and supplemented den stop. Walk-in mechanism (Three-row model): GUID-220	eat in position. Reclining: GUID-22018305-9BAB-4201-B6FC-C08 Seat belts ^o (P.1-9).) The seatback may be reclined to allow occup strap *2 on the lower side of the outboard seats to fold the seatluld result in serious injury in an accident or sudden stopDo not all restraint system 1-5 Condition: 'Except for China'/ [Edit: 2014018305-9BAB-4201-B6FC-C08EB94AEAE0 The second row seats	ants to rest when the vehicle is parked. (23,1) Joack flat. 2.To return the seats to a seating posit fold down the second row seats when occupant 11/7 Model: T32-A]. When returning the seats can tilt and slide for easy entry/ exit to/from the	VR0376X Folding: GUID-22018305-9BAB-4201-B6FC-C08: tion, push up on the seatback until it latches in place. WAI ts are in the second row seat area or any luggage is on the backs to the upright position, be certain they are complet e third row seats. WARNING: After operating the walk-in	EB94AEAE0 1. For vehicles not equipped with third RNING: . Never allow anyone to ride in the luggage as second row seats Properly secure all luggage to be let y secure din the latched position. If they are not comechanism, be sure to return the seat to the rearmant.	row seat: Pull up the lever *1 and fold the seatback flat. For velore or on the rear seats when they are in the fold-down positionally prevent it from sliding or shifting. Do not place luggage higompletely secured, passengers may be injured in an accident or post position and then tilt up the seatback until it latches. CAUTI
void possible injuries and/or damage. When operating the soiled. JVR0355X 1.Pull the lever *1 to tilt down the seatbactors 5-F187F0285680 Folding GUID-F0E0E98B-1F35-427F-AE1 pull straps *1 to raise each seatback. Pull back until the secept for China'/ [Edit: 2014/11/7 Model: T32-A] ARMRES	atback and operate slowly. If the seatback is tilted down quickly walk-in mechanism, be sure that the second row seats are not ock. 2.Slide the seat forward. 3.When returning the seat to its original C-9E5024C736F1 JVR0329X To fold the third row seats flat for atback latches into position. Make sure to properly raise each seat T GUID-0CFA7136-CE0F-460F-B8C8-64D55ED211DE Pull the a	ccupied by passengers and/or any objects to averginal position, slide the seat backward, tilt the seat maximum cargo capacity: 1. Make sure the head eatback to an upright and secured position. WAI rmrest down until it rests on the seat cushion.	oid possible injuries and/or damageDo not operate the weatback up and then secure it in place. 1-6 Safety D seats I restraints are all the way down. 2.Pull the strap *1 to relign RNING: When the seat is returned to the normal seating pVR0337X Second row seats Fold down the armrest while p	alk-in mechanism with objects, drinks, etc. on the s seat belts and supplemental restraint system (24,1 ease the seat. 3.Once released, push the seatback for osition, the head restraints must be returned to the bulling the strap until it rests on the seat cushion. H	eat. This may cause objects to break or cause the passenger roof THIRD ROW SEATS (if equipped) GUID-6AFED800-DD55-423 rward *2 . To return the third row seats to a seating position: Use upright position to properly protect vehicle occupants. Condition EAD RESTRAINTS T32A130827-DB0E9BDD-2C29-4173-B3C0-
craint stalks or remove the head restraint. Do not use the so ous injury or death in a collision. Your vehicle is equipped oper Adjustment: ĐFor the adjustable type, align the head r seed in place before riding in that designated seating positio	ther vehicle safety systems. They may provide additional protect eat if the head restraint has been removed. If the head restraint with a head restraint that may be integrated, adjustable or non-restraint so the center of your ear is approximately level with the n. ADJUSTABLE HEAD RESTRAINT T32A130827-C9F74993-858 D seats, seat belts and supplemental restraint system 1-7 Conditional protections.	was removed, reinstall and properly adjust the ladjustable. Adjustable head restraints have must center of the head restraint. DIf your ear posit BA-41B5-9556-616AFC9796BA SSS0992 1.Remo	head restraint before an occupant uses the seating position ltiple notches along the stalk to lock them in a desired adjoin is still higher than the recommended alignment, place by able head restraint 2. Multiple notches 3. Lock knob 4. States in the state of the states of the states are stated in the states of the states of the states are stated in the states of	n. Failure to follow these instructions can reduce the ustment position. The non-adjustable head restrain the head restraint at the highest position. If the healks NON-ADJUSTABLE HEAD RESTRAINT T32A13	e effectiveness of the head restraint. This may increase the risk ts have single locking notch to secure them to the seat frame. ad restraint has been removed, ensure that it is reinstalled and 0827-2CDD1BB5-1601-41B1-8E92-E1A700D921F6 JVR0203X
EDE4AA04D SSS1038 1.Align the head restraint stalks wit occupant uses the seating position. ADJUST T32A130827-E s. If your ear position is still higher than the recommended se T32A130827-21BF58C9-E66B-43AB-8465-6BA3A92920D	nob. 3.Remove the head restraint from the seat. 4.Store the head has the holes in the seat. Make sure that the head restraint is facil D3FF471-57AE-4DB8-96D1-FF8165FFA3F4 SSS0997 1-8 Safety alignment, place the head restraint at the highest position. JVR04 SSS1035 Type A To raise the head restraint, pull it up. SSS10FA4C1475-83A4-4F07-AB5A-232C4EC6648D SSS1036 To lower	ng the correct direction. The stalk with the adju D seats, seat belts and supplemental restraint of D259X For non-adjustable head restraint Make s D37 Type B To raise the head restraint, push and	stment notch *1 must be installed in the hole with the lock system Condition: 'Except for China'/ [Edit: 2014/11/7 Moure the head restraint is positioned from the stored position hold the lock knob. Then, pull it up. Make sure the head:	k knob *2 . 2.Push and hold the lock knob and push fodel: T32-A] (26,1) For adjustable head restraint A on or any non-latch position so the lock knob is engineerestraint is positioned from the stored position or an	the head restraint down. 3. Properly adjust the head restraint be djust the head restraint so the center is level with the center of aged in the notch before riding in that designated seating positing non-latch position so the lock knob is engaged in the notch be
na'/ (27,1) SEAT BELTS T32A130827-70A68760-75B8-47F3 ry may be greatly reduced. NISSAN strongly encourages y supplemental restraint system Condition: 'Except for Chinavoided. Serious injury may occur if a seat belt is not worn upant; it is danger- ous to put a belt around a child being care.	3-AB2C-B69D82C30139 PRECAUTIONS ON SEAT BELT USAGE ou and all of your passengers to buckle up every time you drive, a'/ [Edit: 2014/11/7 Model: T32-A] WARNING: .Seatbelts are opposerlyPosition the lap belt as low and snug as possible arous arried on the occupant lapNever carry more people in the vehicles.	T32A130827-2F565D7D-05DE-4FB6-B3C3-3001 even if your seating position includes the suppl designed to bear upon the bony structure of the nd the hips, not the waist. A lap belt worn too hiddle than there are seat belts. Never wear seat lateral seat seat seat seat seat seat seat seat	FCA1D36C5 If you are wearing the seat belt properly adjustemental air bag systems. Safety D seats, seat belts and subody, and should be worn low across the front of the pelvigh could increase the risk of internal injuries in an accide belts inside out. Belts should not be worn with straps twist	sted and sitting upright and well back in the seat, c pplemental restraint system 1-9 [Edit: 2014/11/7] is or the pelvis, chest and shoulders, as applicable; ntDo not allow more than one person to use the se ted. Doing so may reduce their effectivenessSeath	nances of being injured or killed in an accident and/or the sever Model: T32-A] SSS0134A SSS0136A 1-10 Safety D seats, seat be wearing the lap section of the belt across the abdominal area makes seat belt. Each belt assembly must only be used by one elts should be adjusted as firmly as possible, consistent with
and your back or under your arm. Always route the shoulded sting devices from operating to remove slack, or prevent to be frayed, contaminated or damaged. All seat belt asserberly. Seat belt assemblies not in use during a collision shows belt has activated, it cannot be reused. It must be replace	esigned. A slack belt will greatly reduce the protection afforded to belt over your shoulder and across your chest. The belt should he seat belt assembly from being adjusted to remove slackCar anblies including retractors and attaching hardware should be in ould also be inspected and, when necessary, replaced if either day do together with the retractor. Contact a NISSAN dealerRemove	be away from your face and neck, but not falling e should be taken to avoid contamination of the spected after any collision by a NISSAN dealer. It is essewal and installation of the pre-ten-sioner seat be	ng off your shoulder. Serious injury may occur if a seat bel webbing with polishes, oils and chemicals, and particular NISSAN recommends that all seat belt assemblies in use ntial to replace the entire assembly after it has been worn lt system components should be done by a NISSAN dealer	t is not worn properlyNo modifications or addition ly battery acid. Cleaning may safely be carried out uduring a collision be replaced unless the collision we in a severe impact even if damage to the assembly c. CHILD SAFETY T32A130827-21B0DB95-14A2-473	s should be made by the user which will either prevent the seat sing mild soap and water. The belt should be replaced if webbins minor and the belts show no damage and continue to operate is not obvious. Condition: 'Except for China'/ .Once the pre-tensis EE-92AA-1384BE5E3511 WARNING: .Infants and children need
y need to be properly restrained. The proper restraint dependent of the manufacturer's instructions for installation and use. It is are too large for a child restraint system should be seated itioned across the top, middle portion of the shoulder and the should	perly. The shoulder belt may come too close to the face or neck. ends on the child's size. Infants and small children T32A130827-Large children T32A130827-080B8EE5-AA4F-4AF7-AC3E-2E92 and restrained by the seat belts that are provided. If the child's he lap belt is low on the hips. The booster seat should also fit the protection. SSS0099 Safety D seats, seat belts and supplementations.	062F78D7-5A66-41DD-980F-C2B540812034 NI 0E4076D3 WARNING: .Never allow children to seating position has a shoulder belt that fits close e vehicle seat. Once the child has grown so that	SSAN recommends that infants and small children be sear stand or kneel on any seatsNever allow children in the ose to the face or neck, the use of a booster seat (commerce the shoulder belt is no longer on or near the face or neck	ted in a child restraint system. You should choose a cargo areas while the vehicle is moving. A child could available) may help overcome this. The booste of the child, use the shoulder belt without the boos	child restraint system that fits your vehicle and the child, and a d be 's seriously injured in an accident or sudden stop. Childre r seat should raise the child so that the shoulder belt is properly ser seat. In addition, there are many types of child restraint systems.
n snug, and always position the lap belt as low as possible SAN recommends that injured persons use seat belts. ConfUTER mark. The center seat belt tongue can be fastened or 2-7A34F4DFC205 WARNING: The seatback should not be feel the latch engage. The retractor is designed to lock d	around the hips, not the waist. Place the shoulder belt over your tact your doctor for specific recommendations. CENTER MARK (ally into the center seat belt buckle. THREE-POINT TYPE SEAT Be in a reclined position any more than needed for comfort. Seat be uring a sudden stop or on impact. A slow pulling motion permits	shoulder and across your chest. Never run the ON SEAT BELTS T32A130827-0794F2A3-5762-4ELTS T32A130827-4BC79D60-6662-49C4-A68E elts are most effective when the passenger sits to the seat belt to move, and allows you some free	lap/ shoulder belt over your abdominal area. Contact your 1467-B86E-B51DB80CB0A0 Selecting correct set of seat be 0-826748688021 SSS0292 WARNING: Every person who evell back and straight up in the seat. 1.Adjust the seat. (Seedom of movement in the seat. 1-12 Safety D seats, seat be	r doctor for specific recommendations. INJURED PE lelts T32A130827-82DC900D-2C78-496F-838E-D25' lrives or rides in this vehicle should use a seat belt a ee aSeatso (P.1-2).) 2.Slowly pull the seat belt out of lelts and supplemental restraint system (30,1). If the	RSONS T32A130827-0BA2B1BE-CCEE-4963-85CA-E7F2231B8 '0976281A SSS0671 The center seat belt buckle is identified by at all times. Fastening seat belts T32A130827-2B97C5AF-CA20-the retractor and insert the tongue into the buckle until you he seat belt cannot be pulled from its fully retracted position, firm
pped) T32A130827-976237C8-B793-46BA-8839-54E163FF ry in an accidentThe shoulder belt should rest on the mid tion best for you. The belt should be away from your face a A130827-6CC264E9-D8AD-4962-9D73-34F9C8D92938 Pus 8-8CD6-FB07919F9DB4 Seat belt retractors are designed	the retractor. SSS0467 3.Position the lap belt portion low and small states and small states and small states are the shoulder. It must not rest against the neck. Be sure the small states and neck, but not falling off your shoulder. To adjust, pull the relation the button on the buckle. The seat belt automatically retracts to lock seat belt movement: When the seat belt is pulled quickly the seat belt is pulled to the seat belt in the seat belt is pulled to the seat belt in the seat	77 Model: T32-A] WARNING: .The shoulder bel hat the seat belt is not twisted in any wayBe s ease button *1 and move the shoulder belt anch Condition: 'Except for China'/ Belt hook (if equations from the retractorWhen the vehicle slows do	t anchor height should be adjusted to the position best for ure that the shoulder belt anchor is secured by trying to n for to the proper position *2, so that the belt passes over ipped) T32A130827-702349E6-D2F9-4807-B5A0-7C9ECOI wn rapidly. To increase your confidence in the seat belts,	you. Failure to do so may reduce the effectiveness nove the shoulder belt anchor up and down after ad the center of the shoulder. Release the button to locate 3E7832 JVR0353X Seat belt can be hooked on the becheck the operation by grasping the shoulder belt a	of the entire restraint system and increase the chance or severing ustment. The shoulder belt anchor height should be adjusted to be the shoulder belt anchor into position. Unfastening seat belts belt hook. Checking seat belt operation T32A130827-71A5C13C-2 and pulling forward quickly. The retractor should lock and restri
her belt movement. If the retractor does not lock during the parts, deterioration, cuts or other damage on the seat be tion recommended for cleaning upholstery or carpet. Then CAUTIONS ON CHILD RESTRAINT USAGE T32A130827-2 arried on your lap. It is not possible for even the strongest	is check, contact a NISSAN dealer immediately. SEAT BELT MAIL webbing is found, the entire seat belt assembly should be replaying with a cloth and allow the seat belts to dry in the shade. DA2A55D3D-261B-4822-A5C9-B00E94E8AA4A SSS0099 WARNING adult to resist the forces of a severe accident. The child could be bear seat than in the front seat. Improper use or improper install	INTENANCE T32A130827-09199535-EE25-4EA laced. If dirt builds up in the shoulder belt guide to not allow the seat belts to retract until they a G: .Infants and small children should always be e crushed between the adult and parts of the vertex.	AC-9D54-D0AED305C354 Periodically check that the seat of the seat belt anchors, the seat belts may retract slowly re completely dry. Safety D seats, seat belts and supplementation of the seat belts and supplementation of the seat belt around both you believe that the same seat belt around both you	belt and all the metal components, such as buckles, v. Wipe the shoulder belt guide with a clean, dry cloental restraint system 1-13 [Edit: 2014/11/7 Modele vehicle. Failure to use a child restraint can result r child and yourselfNISSAN recommends that the	tongues, retractors, flexible wires and anchors, work properly. th. To clean the seat belt webbing, apply a mild soap solution or : T32-A] T32A130827-B9F2FCE8-C8FF-4419-9D1B-47BBBEB8 in serious injury or deathInfants and small children should neather than the child restraints be installed in the rear seat. According to accide
cructions for installation and' suse. When purchasing a child d. Refer to the child restraint manufacturer instructions for traint should not move more than 25 mm (1 in). If the restraint error install a rear-facing child restraint on the front passengutem seriously injure or kill your child. If the seat belt in the	I restraint, be sure to select one which will fit your child and vehing details. 's .Adjustable seatbacks should be positioned to ensuration is not secure, tighten the belt as necessary, or install the respect seat when the front passenger air bag is available. Supplement position where a child restraint is installed requires a locking of	nicle. It may not be possible to properly install so e full contact between child restraint and seatbastraint in another seat and test it again. When to ental front-impact air bags inflate with great force levice and if it is not used, injuries could result to	ome types of child restraint in your vehicleThe direction ackAfter attaching a child restraint, test it before you plane the child restraint is not in use, keep it secured with the IS ce. A rear-facing child restraint could be struck by the sup from a child restraint tipping over during normal vehicle by	of the child restraint, either front-facing or rear-fac- ace the child in it. Push it from side to side and tug is OFIX child restraint system or a seat belt to preven plemental frontimpact air bags in an accident and or raking or cornering. CAUTION: Remember that a c	ing, depends on the type of the child restraint and the size of the triangle to make sure that it is held securely in place. The child it from being thrown around in case of a sudden stop or accide ould 1-14 Safety D seats, seat belts and supplemental restraint hild restraint left in a closed vehicle can become very hot. Check
larger children that should be used for maximum protection hild restraint that complies with the latest European safety nicle's seat belt system. Refer to the tables later in this sect oup III 22 to 36 kg Kind of child seats (example): GUID-2201	d restraint. NISSAN recommends that infants and small children. 's 's Condition: 'Except for China'/ [Edit: 2014/11/7 Model: standard, ECE Regulation 44.04Place your child in the child retion for a list of the recommended fitment positions and the apprairable of the recommended fitment positions. The child safety 18305-9BAB-4201-B6FC-C08EB94AEAE0 JVR0371X Child safety	T32-A] GUID-9BFC6C9D-8671-4D95-8AAD-9E4 estraint and check the various adjustments to be roved child restraints for your vehicle. Mass gro seat categories 0 and 0+ JVR0372X Child safet	C6F1D11F9 UNIVERSAL CHILD RESTRAINTS FOR FROM sure the child restraint is compatible with your child. Always of child seat GUID-40AF683E-378A-45A8-9406-AEFC4.	NT SEAT AND REAR SEATS (for Europe) When seleways follow all of the recommended proceduresCh F5E6253 Mass group Child weight Group 0 up to 10 eat categories II and III Safety D seats, seat belts ar	cting any child restraint, keep the following points in mind: .Ch eck the child restraint in your vehicle to be sure it is compatible kg Group 0+ up to 13 kg Group I 9 to 18 kg Group II 15 to 25 k d supplemental restraint system 1-15 Condition: 'Except for Ch

